



Diffusion design sensor that allows all points of detection to be monitored continuously

Manning AirScan™ iR sensor/transmitter



Refrigerant Specific

- Rapid response to refrigerants including R-404a, R-22, R-507 or R-134a
- Internal monitoring of 4/20 mA loop circuitry continuously

Diffusion-Design Sensor

- Has no moving parts and doesn't require pumps or filters
- All points of detection can be monitored continuously at an affordable cost

Versatility

- Can be used with any Honeywell Analytics readout
- Standard range of 0-3,000 ppm, can be rescaled for lower trip points
- Provides a linear output of 4/20 mA as a function of refrigerant concentration
- Simple, real-time calibration eliminates maintenance downtime
- Automatically adapts to fluctuating temperatures

Long-Lasting Performance

- Unique internal reference channel compensates for dust particles, source degradation, humidity and temperature fluctuation, food odours, chemical cleaners, etc.

ATMOS™ Technology

- Allows for operation down to -40°F and in condensing humidity environments or during washdown
- Automatically adapts to its environment and provides accurate and reliable performance under the harshest conditions

SensorCheck™ Technology

- Checks operating parameters of sensors and sends a notification output signal if an anomaly is identified
- Tests the sensor every 24 hours for electrical viability
- Indication can be detected by a Manning gas monitor or PLC

Housing

- High-mass metal bench provides structural and thermal stability and greater immunity to vibration
- Superior EMI/RFI shielding

The Manning AirScan™ iR sensor responds to refrigerants over the range of 0-3000 ppm and features SensorCheck™ technology that continually monitors sensor performance.

The Manning AirScan™ iR infrared sensor is an affordable microprocessor-based sensor that is selective to refrigerants and, because of its stabilized design platform, will provide years of service and will maintain the highest level of accuracy and reliability. This highly versatile sensor features SensorCheck™, a unique technology that continuously monitors sensor performance that enables it to provide worry-free performance

throughout the life of the sensor. A true "diffusion" design sensor, the Manning AirScan™ iR sensor does not require either pumps or filters and allows all points of detection to be monitored perpetually, unlike sample draw systems. The versatile sensor is housed in a high mass metal bench structure that enables thermal stability and freedom from vibration.

Applications

- Banana and Produce Rooms
- Beverage Plants
- Chemical Plants
- Confined Space Entry
- Food Processing
- Gas Bottling Plants
- Ice Rinks
- Product Coolers
- Rack Houses
- Refrigeration Systems
- Supermarkets
- Wineries



Technical summary



General Specification	
Use	Infrared (diffusion) type sensor that works in conjunction with any Honeywell Analytics Manning readout or alarm unit. This sensor is selective to refrigerants including R-404a, R-22, R-507 or R-134a. Can sense refrigerants over the range of 0-3,000 ppm and can be re-scaled to 0-500 if lower trip points are needed.
Common Operation	
Gases Monitored	R-404a, R-22, R-507, R-134a
Gas Sampling	Diffusion method with no moving parts, real time continuous monitoring of all points
Output	Linear 4/20 mA output into a load resistor of 500 ohm maximum
Accuracy	+/- 3% full scale
Repeatability	+/- 1% full scale
Operational	
Humidity	0-100% RH (condensing)
Operating Temperature	-40°C to +60°C / -40°F to +140°F
Storage Temperature	-28°C to +60°C / -20°F to +140°F
Common Module	
Cable Recommendation	Three conductor, stranded shielded cable with drain wire, all enclosed in a vinyl jacket. For cable runs up to 200 feet, use 18# AWG (Belden #8770 or equivalent). For cable runs up to 1,000 feet, use #16 AWG (Belden #8618 or equivalent).
Power Source	24 Volts DC regulated, 1.0 amp
Repeatability	+/- 1% full scale
Sensor Specifications	
Response Time	T90 = 10 seconds with full-scale calibration gas @ .75 litres/min. flow rate
Ranges	0-3,000 ppm (standard) can be re-scaled to 0-500 ppm if lower trip points are needed
Sensor Viability Test	SensorCheck, an internal microprocessor determines the sensor's electrical viability every 24 hours. If the viability test fails a 0.5 mA signal will indicate a fault. An internal light will show if a sensor is dried up or disconnected.
Enclosure	NEMA 4, gasketed, molded fiberglass reinforced polyester. Non-painted, non-rusting construction appropriate for food areas. UL 508 listed, CSA certified for use with industrial control equipment.
Weight	4.4 lbs.

As world leaders in gas detection solutions, Honeywell Analytics' Manning range of gas detection systems has been designed to provide efficient, practical and cost-effective equipment to protect people from a variety of forms of hazardous gas and to efficiently monitor and control indoor air quality. The equipment is also simple to install and easy to operate and maintain.

The Manning range of fixed gas detection and accessories



ManningGM-JR



Manning EC-F9-NH3



Manning GM-1



Manning GM-10



Manning AirAlert™ 96d

Manning Line of Sensors

Designed for both industrial and commercial environments, the Manning line of sensors are produced to withstand the harshest of environments. The electrochemical and infrared sensors can be configured with the optional ATMOS® equipped technology that allows them to meet all of their performance specifications down to -50° F and in condensing humidity environments or during washdown.

Find out more

For more information on Honeywell Analytic's Manning line of products, visit www.honeywellanalytics.com or contact us at 800 444 9935

Customer business center

USA, Central and South America

Honeywell Analytics
23500 West 105th Street, MD 400
Olathe, KS
66061-6615
Tel: +1 913 894 1185
Toll free: +1 800 444 9935
Fax: +1 888 328 2417
detectgas@honeywell.com
www.honeywell.com

Customer business center

Canada

Honeywell Analytics
4005 Matte Blvd., Unit G
Brossard, QC, Canada
J4Y 2P4
Toll free: +1 800 563 2967
Tel: +1 450 619 2450
Fax: +1 888 967 9938
detectgas@honeywell.com
www.honeywell.com

Customer business centre

Europe and the rest of the world

Honeywell Analytics
Wilstrasse 11-U11
CH-8610 Uster
Switzerland
Tel: +41 (0) 44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com
www.honeywell.com

Manning Controllers

Regardless of the number of sensors that need to be monitored, there is a Honeywell Analytics Manning controller system that will suit your needs. These multi-channel stand-alone monitoring/safety systems support up to ten (10) Honeywell Analytics gas detection sensors each and can interface with the plant central safety controls. Modular construction allows easy addition of up to forty (40) extra relay outputs and individual 4/20 mA signal output from each channel.



Calibration Kit

The do-it-yourself solution for recommended calibration of Manning fixed line of gas detection products enables the product to be recertified for the required sensor recalibration. This easy to use kit contains everything needed for simple calibration including gas cylinders containing applicable gas, a calibration adaptor, flow meter, valve assembly, and tubing housed in a durable carrying case.

Honeywell